

# Distributed Systems

## Principles and Paradigms

Maarten van Steen

VU Amsterdam, Dept. Computer Science  
Room R4.20, steen@cs.vu.nl

## Chapter 01: Introduction

Version: August 27, 2012




# Distributed System: Definition

A distributed system is

*a collection of **autonomous computing elements** that appears to its users as a **single coherent system***

Two aspects: (1) independent computing elements and  
(2) single system  $\Rightarrow$  **middleware**.



# Goals of Distributed Systems

- Making resources available
- Distribution transparency
- Openness
- Scalability

# Distribution transparency

Transp.	Description
Access	Hide differences in data representation and how an object is accessed
Location	Hide where an object is located
Relocation	Hide that an object may be moved to another location while in use
Migration	Hide that an object may move to another location
Replication	Hide that an object is replicated
Concurrency	Hide that an object may be shared by several independent users
Failure	Hide the failure and recovery of an object

## Note

Distribution transparency is a nice a goal, but achieving it is a different story.

# Degree of transparency

## Observation

Aiming at full distribution transparency may be too much:

- Users may be located in **different continents**
- **Completely hiding failures** of networks and nodes is (theoretically and practically) **impossible**
  - You cannot distinguish a slow computer from a failing one
  - You can never be sure that a server actually performed an operation before a crash
- Full transparency will **cost performance**, exposing distribution of the system
  - Keeping Web caches **exactly** up-to-date with the master
  - Immediately flushing write operations to disk for fault tolerance

# Openness of distributed systems

## Open distributed system

Be able to interact with services from other open systems, irrespective of the underlying environment:

- Systems should conform to well-defined **interfaces**
- Systems should support **portability** of applications
- Systems should easily **interoperate**

## Achieving openness

At least make the distributed system independent from **heterogeneity** of the underlying environment:

- Hardware
- Platforms
- Languages

# Policies versus mechanisms

## Implementing openness

Requires support for different **policies**:

- What level of consistency do we require for client-cached data?
- Which operations do we allow downloaded code to perform?
- Which QoS requirements do we adjust in the face of varying bandwidth?
- What level of secrecy do we require for communication?

## Implementing openness

Ideally, a distributed system provides only **mechanisms**:

- Allow (dynamic) setting of caching policies
- Support different levels of trust for mobile code
- Provide adjustable QoS parameters per data stream
- Offer different encryption algorithms

# Scale in distributed systems

## Observation

Many developers of modern distributed system easily use the adjective “scalable” without making clear **why** their system actually scales.

## Scalability

At least three components:

- Number of users and/or processes (size scalability)
- Maximum distance between nodes (geographical scalability)
- Number of administrative domains (administrative scalability)

## Observation

Most systems account only, to a certain extent, for size scalability. The (non)solution: powerful servers. Today, the challenge lies in geographical and administrative scalability.

# Techniques for scaling

## Hide communication latencies

Avoid waiting for responses; do something else:

- Make use of **asynchronous communication**
- Have separate handler for incoming response
- **Problem:** not every application fits this model

# Techniques for scaling

## Distribution

Partition data and computations across multiple machines:

- Move computations to clients (Java applets)
- Decentralized naming services (DNS)
- Decentralized information systems (WWW)

# Techniques for scaling

## Replication/caching

Make copies of data available at different machines:

- Replicated file servers and databases
- Mirrored Web sites
- Web caches (in browsers and proxies)
- File caching (at server and client)

# Scaling – The problem

## Observation

Applying scaling techniques is easy, except for one thing:

- Having multiple copies (cached or replicated), leads to **inconsistencies**: modifying one copy makes that copy different from the rest.
- Always keeping copies consistent and in a general way requires **global synchronization** on each modification.
- Global synchronization precludes large-scale solutions.

## Observation

If we can tolerate inconsistencies, we may reduce the need for global synchronization, but **tolerating inconsistencies is application dependent**.

# Developing distributed systems: Pitfalls

## Observation

Many distributed systems are needlessly complex caused by mistakes that required patching later on. There are many **false assumptions**:

- The network is reliable
- The network is secure
- The network is homogeneous
- The topology does not change
- Latency is zero
- Bandwidth is infinite
- Transport cost is zero
- There is one administrator

# Types of distributed systems

- Distributed computing systems
- Distributed information systems
- Distributed pervasive systems

# Distributed computing systems

## Observation


Many distributed systems are configured for **High-Performance Computing**

## Cluster Computing

Essentially a group of high-end systems connected through a LAN:

- Homogeneous: same OS, near-identical hardware
- Single managing node

# Distributed computing systems



# Distributed computing systems

## Grid Computing


The next step: lots of nodes from everywhere:

- Heterogeneous
- Dispersed across several organizations
- Can easily span a wide-area network

## Note

To allow for collaborations, grids generally use [virtual organizations](#). In essence, this is a grouping of users (or better: their IDs) that will allow for authorization on resource allocation.

# Distributed computing systems: Clouds



# Distributed computing systems: Clouds

## Cloud computing

Make a distinction between four layers:

- **Hardware**: Processors, routers, power and cooling systems. Customers normally never get to see these.
- **Infrastructure**: Deploys virtualization techniques. Evolves around allocating and managing virtual storage devices and virtual servers.
- **Platform**: Provides higher-level abstractions for storage and such. Example: Amazon S3 storage system offers an API for (locally created) files to be organized and stored in so-called **buckets**.
- **Application**: Actual applications, such as office suites (text processors, spreadsheet applications, presentation applications). Comparable to the suite of apps shipped with OSes.

# Distributed Information Systems

## Observation

The vast amount of distributed systems in use today are forms of traditional information systems, that now **integrate** legacy systems.

**Example:** Transaction processing systems.

```
BEGIN_TRANSACTION(server, transaction)
READ(transaction, file-1, data)
WRITE(transaction, file-2, data)
newData := MODIFIED(data)
IF WRONG(newData) THEN
    ABORT_TRANSACTION(transaction)
ELSE
    WRITE(transaction, file-2, newData)
    END_TRANSACTION(transaction)
END IF
```

## Note

Transactions form an **atomic** operation.

# Distributed information systems: Transactions

## Model

A transaction is a collection of operations on the state of an object (database, object composition, etc.) that satisfies the following properties (**ACID**)

**Atomicity:** All operations either succeed, or all of them fail. When the transaction fails, the state of the object will remain unaffected by the transaction.

**Consistency:** A transaction establishes a valid state transition. This does not exclude the possibility of invalid, intermediate states during the transaction's execution.


**Isolation:** Concurrent transactions do not interfere with each other. It appears to each transaction  $T$  that other transactions occur either **before**  $T$ , or **after**  $T$ , but never both.

**Durability:** After the execution of a transaction, its effects are made permanent: changes to the state survive failures.

# Transaction processing monitor

## Observation


In many cases, the data involved in a transaction is distributed across several servers. A **TP Monitor** is responsible for coordinating the execution of a transaction



# Distr. info. systems: Enterprise application integration

## Problem

A TP monitor doesn't separate apps from their databases. Also needed are facilities for direct communication between apps.



- Remote Procedure Call (RPC)
- Message-Oriented Middleware (MOM)

# Distributed pervasive systems

## Observation

Emerging next-generation of distributed systems in which nodes are small, mobile, and often embedded in a larger system, characterized by the fact that the system **naturally blends into the user's environment**.

## Three (overlapping) subtypes

- **Ubiquitous computing systems**: pervasive and **continuously present**, i.e., there is a continuous interaction between system and user.
- **Mobile computing systems**: pervasive, but emphasis is on the fact that devices are **inherently mobile**.
- **Sensor (and actuator) networks**: pervasive, with emphasis on the actual (collaborative) **sensing** and **actuation** of the environment.

# Ubiquitous computing systems

## Basic characteristics

- (**Distribution**) Devices are networked, distributed, and accessible in a transparent manner
- (**Interaction**) Interaction between users and devices is highly unobtrusive
- (**Context awareness**) The system is aware of a user's context in order to optimize interaction
- (**Autonomy**) Devices operate autonomously without human intervention, and are thus highly self-managed
- (**Intelligence**) The system as a whole can handle a wide range of dynamic actions and interactions

# Mobile computing systems

## Observation

Mobile computing systems are generally a subclass of ubiquitous computing systems and meet all of the five requirements.

## Typical characteristics

- Many different types of mobile devices: smart phones, remote controls, car equipment, and so on
- Wireless communication
- Devices may continuously change their location ⇒
  - setting up a route may be problematic, as routes can change frequently
  - devices may easily be temporarily disconnected ⇒  
**disruption-tolerant networks**

# Sensor networks

## Characteristics

The **nodes** to which sensors are attached are:

- Many (10s-1000s)
- Simple (small memory/compute/communication capacity)
- Often battery-powered (or even battery-less)

# Sensor networks as distributed systems

